

Plugs

BUELA 300 K



| Product | BUELA 300 K |
|---|---|
| description | Multiple-spring wire plug, shatter-proof, flexible insulated sleeve with transverse hole. Lateral supports provide protection against contact when plugged in at right angles. The tapering sleeve end also serves as kinking protection for the lead. Solder connection up to maximum cable cross-section of 2.5 mm ² . |
| operating instruction | BA409 |
| article-no. / *colour | 9316671xx <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">● 00 black</div> <div style="text-align: center;">● 01 red</div> <div style="text-align: center;">● 02 blue</div> <div style="text-align: center;">● 03 yellow</div> <div style="text-align: center;">● 04 green</div> </div> <div style="text-align: right; border: 1px solid black; padding: 2px; margin-top: 5px;">Ni</div> |
| drawing | |
| | |
| technical data | |
| connection | solder connection |
| rated voltage | 30 VAC / 60 VDC |
| measurement cat. acc. to IEC 61010 | O ⁽²⁾ |
| rated current (consider derating curve) | 30 A |
| material plug | brass, nickel plated |
| housing material | PVC-P |
| temperature range acc. To IEC61010 ⁽¹⁾ | -25 °C to +70 °C |

⁽¹⁾ contact the manufacturer for applications at deviating temperature ranges

⁽²⁾ without rated measurement category, for other circuits that are not directly connected to mains

stand: 21.06.2022

stand: 21.06.2022